



Click [here](#) for the 3D model.

| Dimensions | |
|------------|-----------------|
| L | 41.5mm -0.7mm |
| H | 40mm -0.7mm |
| T | 20mm -0.7mm |
| S | 37.5mm +/-0.4mm |
| S1 | 10.2mm +/-0.4mm |
| LL | 6mm -2mm |
| F | 1.2mm NOM |

| Packaging Specifications | |
|--------------------------|-----------|
| Packaging | Bulk, Bag |
| Packaging Quantity | 58 |

| General Information | |
|---------------------|--------------------------|
| Series | C4AT |
| Dielectric | Metallized Polypropylene |
| Style | Radial |
| Features | Switching |
| RoHS | Yes |
| Lead | 4 Wire Leads |
| AEC-Q200 | No |
| Component Weight | 45.34 g |

| Specifications | |
|-----------------------|---------------------------------------|
| Capacitance | 10 uF |
| Capacitance Tolerance | 5% |
| Voltage AC | 250 VAC |
| Voltage DC | 400 VDC |
| Temperature Range | -40/+85°C |
| Rated Temperature | 70°C |
| Dissipation Factor | 0.05% |
| Max dV/dt | 50 V/us |
| Resistance | 2.2 mOhms (100kHz) |
| Ripple Current | 28 Amps (100kHz 70C), 502 Amps (Peak) |