



Product Change Notification / SYST-09IWPZ106

Date:

10-Aug-2022

Product Category:

Ethernet Switches

PCN Type:

Document Change

Notification Subject:

Data Sheet - KSZ9567R Data Sheet

Affected CPNs:

[SYST-09IWPZ106_Affected_CPN_08102022.pdf](#)

[SYST-09IWPZ106_Affected_CPN_08102022.csv](#)

Notification Text:

SYST-09IWPZ106

Microchip has released a new Datasheet for the KSZ9567R Data Sheet of devices. If you are using one of these devices please read the document located at [KSZ9567R Data Sheet](#).

Notification Status: Final

Description of Change:

- Section 5.1.4.7.2, "Global PM Available Register" The following has been defeatured in the document: 'low latency cut through mode' and 'time aware traffic scheduler per port'.
- Table 3-2, "Pin Descriptions" Updated Port Receive Error pin definition: from "MII Mode" to "MII/RMII Modes" and "RMII/RGMII Modes" to "RGMII Mode".
- Table 3.2.1, "Configuration Straps" Updated strapping pin high instructions from "a non-LED pin" to "any pin".
- Table 3-3, "Configuration Strap Descriptions" Updated In-Band Management to include the following note: "If using I2C, do not enable IBA."
- Section 4.1.7, "Auto-Negotiation" Updated auto-negotiation bypass paragraph, changing "operating mode" to "operating speed". Also added this sentence to the end of the paragraph: "With parallel detection, the duplex will always be half-duplex."
- Section 5.1.1.6, "Global Interrupt Status Register" Updated field 29:0 definition: from "Reserved" to "APB Timeout Interrupt Status".
- Section 5.1.1.7, "Global Interrupt Mask Register" Updated field 29:0 definition: from "Reserved" to "APB Timeout Interrupt Mask".
- Section 5.1.2.3, "In-Band Management (IBA) Control Register" Updated bit 31 IBA Enable definition to add the following note: "If using I2C, do not enable IBA."
- Section 5.1.4.7.2, "Global PM Available Register" Added new register to accommodate Packet Memory Available Block Count.

-Section 5.1.6.1, "Global PTP Clock Control Register" Added the following note to bit 1 definition: "The PTP Clock must be enabled when using the time stamp units (TSU) or trigger output units (TOU), even if IEEE 1588 is not implemented."

-Section 5.1.6.21, "Trigger Output Unit Control 2 Register" Added the following note to the definition of bits 0- 31: "The minimum value for this parameter is 0x50."

-Section 5.1.6.24, "Trigger Output Unit Control 5 Register" Removed the following sentence from the description of this register: "This register contains the PTP event trigger output PPS signal pulse width for unit 2 and path delay compensation for unit 1."

-Section 5.2.2.21, "Port Special Register" Added new register to accommodate Single-LED Mode Workaround Bit.

-Section 5.2.7.4, "Port Authentication Control Register" Updated bit 2 Access Control List (ACL) Enable definition from "0 = enable" to "0 = disable".

-Section 5.2.8.3, "Port Transmit Queue Control 0 Register" Updated bits 4-5 Shaper Mode definition from: "10 = Time aware shaper (TAS) per IEEE 802.1Qbv for TSN" to "Reserved".

-Section 5.2.9.3, "Port Transmit Queue Memory Register" Added new register to accommodate Port N Transmit Queue Blocks Used.

-Section 5.4.1, "MMD LED Mode Register" Updated bit 4 definition by adding the following sentence: "For Single-LED mode, set this bit and also set bit 9 in register 0xN13C-0xN13D."

-Table 5-3, "Data Rate Selection Table for Ingress and Egress Rate Limiting" Updated 7d'1 - 7d'10 1000Mbps BPS definition from "1Mbps" to "10Mbps".

-Section 6.4.8, "Power-up and Reset Timing" For Note 3, updated first sentence from: "The recommended power down sequence is to power down the low voltage core before powering down the transceiver and digital I/O voltages, or to have all supplies power down in unison" to "The power supplies may be powered down in any sequence."

Impacts to Data Sheet: See above details.

Change Implementation Status: Complete

Date Document Changes Effective: 10 Aug 2022

NOTE: Please be advised that this is a change to the document only the product has not been changed.

Markings to Distinguish Revised from Unrevised Devices: N/A

Attachments:

[KSZ9567R Data Sheet](#)

Please contact your local [Microchip sales office](#) with questions or concerns regarding this notification.

Terms and Conditions:

If you wish to receive Microchip PCNs via email please register for our PCN email service at our [PCN home page](#) select register then fill in the required fields. You will find instructions about registering for Microchips PCN email service in the [PCN FAQ](#) section.

If you wish to change your PCN profile, including opt out, please go to the [PCN home page](#) select login and sign into your myMicrochip account. Select a profile option from the left navigation bar and make the applicable selections.

Affected Catalog Part Numbers (CPN)

KSZ9567RTXI

KSZ9567RTXI-TR